

Specifications	SCORCPION
TOWER AVAILABLE WITH TRAILER UNIT	T2-100UG T2-85UG T2-60UG T-35UG T- 40UG T-50UG T-60UG T-75UG T-85UG T-100UG
ALUMINUM SHELTER SIZE	N/A
TRAILER WIDTH OVERALL	90 ½ IN
TRAILER WIDTH, FRAME ONLY	86 IN
TRAILER DECK HEIGHT	23 IN
GROUND CLERANCE	19 IN
TRAILER LENGTH OFTALL (W/O COUPLER)	300 1/8 IN
TRAILER GROSS VEHICLE WGHT (GVWR)	10,000 - 11,900
TRAILER GROSS AXLE WGHT (GAWR)	10,400 - 12,000
TRAILER <u>APPROX</u> . WEIGHT SHIPPED (VARIES WITH DIFFERENT ACCESSORIES)	8000 LBS
NUMBER OF AXLES	2
AXLE CAPACITY RATING (EACH)	5,200 OR 6,000
COUPLER CHANNEL (POSITIONS/HOLES)	5/6
STANDARD COUPLER SIZE	2 5/16 IN BALL
BRAKES	Y
TIRE SIZE (NOTE: ALL RADIAL TIRES!)	LT 235 / 85R / 16
TIRE LOAD RANGE	E
WHEEL / RIM SIZE (DIA./WIDTH/BOLT PATTERN)	16
SHELTER ON TRAILER HEIGHT	N/A
OVERALL LENGTH WITH TOWER MOUNTED	387 ½ IN
UID Label MIL-STD-130	Yes



Aluma Tower Company, Inc. reserves the right to make changes at any time to information contained in this document.